



HALSPAN



Halspan 60 Minute Fire Seal for Timber Frames



Halspan have developed a range of fire seals to complement our range of fire rated door blanks. These fire seals have been tested to BS476: Part 22 performance to 60 minutes fire resistance.



Fire 60 min

Tested in Accordance with:

BS476: Part 22



Product Codes & Specifications

Colour	Product Code	
	2100mm lengths	2500mm lengths
● Brown	BOM-T60-100-21BR	BOM-T60-100-25BR
● Black	BOM-T60-100-21BK	BOM-T60-100-25BK
○ White	BOM-T60-100-21WH	BOM-T60-100-25WH

Section



General Maintenance & Operational Notes

Care must be taken to ensure that these seals are used in the correct manner, in accordance with certification data such as Field of Application Reports and primary test evidence.

Further industry guidance can also be found in the following publications:

- BS 8214:2016: Timber-based fire door assemblies - Code of practice
- BS 9999:2017: Fire safety in the design, management and use of buildings – Code of practice
- ASDMA - Guidance and Recommendations for the Coordination of Bespoke Doorsets
- ASDMA - Best Practice Guide to Timber Fire Doors

Supporting Certification and Test Data

Warringtonfire Halspan Optima 60 Field of Application Report Chilt/A01205

Warringtonfire Halspan Prima 60 Field of Application Report FEA/F96103

The information in this datasheet is correct at time of going to press. However our designs, specifications and certifications may change in the interest of product development following publication. If you would like to make a query about any of the details in this document, please contact Halspan via our website, or call our office in the UK on +44 (0)3300 563836.

