



Prima 38mm Interior Grade Door Blanks

Prima 38mm internal fire door blanks feature Halspan's unique 3-layer particle board. Specifically designed for the purpose, using a complex combination of chemical and engineering development, these blanks produce doors of altogether superior quality, strength and overall performance. When bonded up, this blank can achieve FD30 fire rating.



Fire Rating FD30

Tested in Accordance with:	BS 476: Part 22* *FD30 fire rating when suitably bonded up with additional facings, as per relevant fire certification.		
Maximum Approved Sizes* * Please refer to certification reports for the corresponding widths and heights and full permitted details	Single Doors	Maximum height: 2872mm* Maximum width: 1136mm*	
	Double Doors	Maximum width: 2772mm* Maximum width: 1077mm*	
Approved Frames	Timber Hardwood, Timber Softwood, MDF		
Approved Glazing Size	0.5m ²		



Design Criteria

Stock Board Sizes* *Bespoke sizes are available on request. *Prima is also available in other thickness upon request, if required.	<ul style="list-style-type: none"> • 2135mm x 915mm • 2440mm x 1220mm
-------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------



General Properties

Weight	24kg/m ²
Density (±10%)	630kg/m ³ +/- 10%
Moisture Content	Ex factory 6-12%

Supporting Certification and Test Data

Warringtonfire Halspan Prima 30 Field of Application Report FEA/F97174 Part 3
IFC/Kiwa Halspan Prima 30 Field of Application Report IFCA/06166

The information in this datasheet is correct at time of going to press. However our designs, specifications and certifications may change in the interest of product development following publication. If you would like to make a query about any of the details in this document, please contact Halspan via our website, or call our office in the UK on +44 (0)3300 563836.

